



CTEMAX

CTEMAX sNAND WITH HS400 INTERFACE

SPECIFICATION V1.21

CTE8GABF

CTE16GADF

CTE32GDSA

CTE64GDEF

Contents

1. Product List	- 6 -
2. Key Features	- 6 -
3. Package Configurations.....	- 8 -
3.1 BGA 153 Ball Pin Configurations	- 8 -
3.2 Pins and Signal Description.....	- 9 -
3.3 BGA 11.5mm x 13mm x 1.0mm Package Dimension.....	- 10 -
3.4 Product Block Diagram	- 10 -
4. S/W Algorithm	- 11 -
4.1 Partition Management.....	- 11 -
4.2 Enhanced Partition (Area)	11
4.3 User Density.....	- 11 -
4.4 Typical Performance	- 12 -
4.5 Power Consumption.....	- 12 -
5. sNAND Features Overview.....	- 14 -
5.1 HS400 Interface.....	- 14 -
5.2 Field Firmware Upgrade (FFU)	- 15 -
5.3 Cache	- 15 -
5.4 Discard.....	- 15 -
5.5 Power off Notification.....	- 15 -
5.6 Packed Commands.....	15
5.7 Sleep (CMD5).....	- 15 -
5.8 Enhanced Reliable Write.....	- 16 -
5.9 Sanitize	- 16 -
5.10 Secure Erase.....	- 16 -
5.11 Secure Trim.....	- 16 -
5.12 High Priority Interrupt (HPI)	- 16 -
5.13 H/W Reset	- 17 -
5.14 Command Queue.....	- 17 -
6. Register Value	- 18 -
6.1 OCR Register.....	- 18 -
6.2 CID Register	- 18 -
6.3 DSR Register	- 18 -

6.4 CSD Register.....	- 19 -
6.5 EXT_CSD Register	- 20 -

7. Electrical Characteristics- 26 -

7.1 Supply Voltage.....	- 26 -
7.2 Bus Signal Levels	- 26 -
7.3 Bus Timing in Single Data Rate Mode.....	- 27 -
7.4 Bus Timing in HS200 Mode	- 29 -
7.5 Bus Timing in HS200 Mode	- 30 -
7.6 Bus Timing in HS400 Mode	- 33 -

如需获取完整版规格书
请联系我司岳经理
电话：18138426570
微信二维码如下：



Linda

